


Euro - Tight

Euro - Tight

Material Messing, vernickelt **Dichteinsatz** Nitril oder Silikon **Schutzart** IP 68 -5bar (30 min.)
Temperaturen von -40°C bis +100°C **O-Ring** Perbunan (NBR) **Hinweis**

Material Nickel plated brass **Sealing** Nitrile or silicone **Protection Class** IP 68 -5bar (30 min.)
Temperatures from -40°C to +100°C **O-Ring** Perbunan (NBR) **Note**

Artikel / Article	Größe / Size AG	Klemmbereich / Clamping Range		Form / Type		L	VPE / PU
		≥	≤				
Nitril-Dichteinsatz / nitrile sealing							
63080512	M 12 x 1,5	4.0	6.0	A	14	5.0	50
63080516	M 16 x 1,5	4.0	9.0	A	18	5.0	50
63080520	M 20 x 1,5	7.0	13.0	A	22	6.0	50
63080525	M 25 x 1,5	10.0	18.0	A	28	7.0	25
63080532	M 32 x 1,5	16.0	24.0	A	35	8.0	20
63080540	M 40 x 1,5	22.0	32.0	A	45	8.0	20
63080575	M 75 x 1,5	56.0	65.0	B	77	16.0	1
63080580	M 80 x 2,0	62.0	66.0	B	90	18.0	1
63080585	M 85 x 2,0	67.0	77.0	B	95	22.0	1

