

# Euro - Top Edelstahl

IP68 - Kabelverschraubung / cable gland stainless steel

**Material** Edelstahl (303/1.4305)  
**Temperaturen** von -40°C bis +100°C



**Dichteinsatz** Neoprene  
**Klemmeinsatz** Polyamid 6  
**O-Ring** Perbunan (NBR)

**Schutzart** IP 68 -5bar (30 min.), IP 69k  
**Hinweis** integrierte Zugentlastung  
EN 50262


**Material** Stainless Steel (303/1.4305)  
**Temperatures** from -40°C to +100°C



**Sealing** Neoprene  
**Clamping Insert** Polyamide 6  
**O-Ring** Perbunan (NBR)

**Protection Class** IP 68 -5bar (30 min.)  
**Note** integrated strain relief  
EN 50262

Artikel / Article	Größe / Size	Klemmbereich / Clamping Range				L	VPE / PU
		≥	≤				
Standarddichteinsatz / standard sealing							
90080512	M 12 x 1,5	3	6,5	14	14	6.0	50
90080516	M 16 x 1,5	4	8	17	19	7.0	50
90080520	M 20 x 1,5	6	12	22	22	8.0	50
90080525	M 25 x 1,5	10	14	24	27	8.0	25
90080532	M 32 x 1,5	13	18	30	36	9.0	20
90080540	M 40 x 1,5	18	25	41	46	9.0	20
90080550	M 50 x 1,5	22	32	50	55	9.0	15
90080563	M 63 x 1,5	34	44	65	70	14.0	12

Auch in V4A - 1.4404 lieferbar. / Also deliverable in 316L - 1.4404.



Artikel / Article	Größe / Size	Klemmbereich / Clamping Range				L	VPE / PU
		≥	≤				
Reduzierdichteinsatz / reducing sealing							
90180512	M 12 x 1,5	2	5	14	14	6.0	50
90180516	M 16 x 1,5	2	6	17	19	7.0	50
90180520	M 20 x 1,5	5	9	22	22	8.0	50
90180525	M 25 x 1,5	7	12	24	27	8.0	25
90180532	M 32 x 1,5	9	16	30	36	9.0	20
90180540	M 40 x 1,5	12	20	41	46	9.0	20
90180550	M 50 x 1,5	20	26	50	55	9.0	15
90180563	M 63 x 1,5	32	42	65	70	14.0	12



Auch in V4A - 1.4404 lieferbar. / Also deliverable in 316L - 1.4404.

# Euro - Top Edelstahl


IP68 - Kabelverschraubung / cable gland stainless steel



<b>Material</b>	Edelstahl (303/1.4305)	<b>Dichteinsatz</b>	Neoprene	<b>Schutzart</b>	IP 68 -5bar (30 min.), IP 69k
<b>Temperaturen</b>	von -40°C bis +100°C	<b>Klemmeinsatz</b>	Polyamid 6	<b>Hinweis</b>	integrierte Zugentlastung
		<b>O-Ring</b>	Perbunan (NBR)		EN 50262

<b>Material</b>	Stainless Steel (303/1.4305)	<b>Sealing</b>	Neoprene	<b>Protection Class</b>	IP 68 -5bar (30 min.)
<b>Temperatures</b>	from -40°C to +100°C	<b>Clamping Insert</b>	Polyamide 6	<b>Note</b>	integrated strain relief
		<b>O-Ring</b>	Perbunan (NBR)		EN 50262

Artikel / Article	Größe / Size	Klemmbereich / Clamping Range				L	VPE / PU
		≥	≤				
Standarddichteinsatz / standard sealing							
90080407	PG 7	3	6.5	14	14	6.0	50
90080409	PG 9	4	8	17	17	6.0	50
90080411	PG 11	5	10	22	22	6.0	50
90080413	PG 13.5	6	12	22	22	6.5	50
90080416	PG 16	10	14	24	24	6.5	25
90080421	PG 21	13	18	30	30	7.5	25
90080429	PG 29	18	25	41	41	8.0	20
90080436	PG 36	22	32	50	50	9.0	15
90080442	PG 42	30	38	60	60	12.0	12
90080448	PG 48	34	44	65	65	14.0	12

Auch in V4A - 1.4404 lieferbar. / Also deliverable in 316L - 1.4404.



Artikel / Article	Größe / Size	Klemmbereich / Clamping Range				L	VPE / PU
		≥	≤				
Reduzierdichteinsatz / reducing sealing							
90180407	PG 7	2	5	14	14	6.0	50
90180409	PG 9	2	6	17	17	6.0	50
90180411	PG 11	3	7	22	22	6.0	50
90180413	PG 13.5	5	9	22	22	6.5	50
90180416	PG 16	7	12	24	24	6.5	25
90180421	PG 21	9	16	30	30	7.5	25
90180429	PG 29	12	20	41	41	8.0	20
90180436	PG 36	20	26	50	50	9.0	15
90180442	PG 42	25	31	60	60	12.0	12
90180448	PG 48	29	35	65	65	14.0	12

Auch in V4A - 1.4404 lieferbar. / Also deliverable in 316L - 1.4404.